

GERDA[®]



ALUMINUM EXTERIOR DOORS

ALTUS



tedee powered by GERDA

Page 3

GERDA Over 35 years of experience

Page 4-5

Why choose GERDA Aluminum Doors?

Page 6-7

ALTUS Door Collection

Page 8-9

ALTUS Door Designs

Page 10-18

Dimensions of door frames

Page 20

Side and top lights

Page 21

Colours

Page 22

Accessories

Page 23

Inspirations

Page 24-27



Unlock your door with a smartphone

Open and close doors and check lock status from anywhere in the world.

Thanks to the automatic opening function, you do not have to take your smartphone out of your pocket or purse.

The lock will detect your presence and let you in. Analogically, you can use the self-locking function.

Efficient battery

In cooperation with the South Korean Research Institute, Gerda engineers have developed a dedicated and extremely efficient small-sized battery.

The battery provides electricity for half a year of mechanism operation. When there is a need for charging, you will be notified by the lock. You can charge the battery in just one night.

Safety warranty

The mechanism that drives the lock is an innovative and patented structure designed by Gerda engineers.

The software was created by IoT experts from tedee. Owing to this intuitive app, you can track who has been locking or opening the door and when or grant remote virtual keys.

Tedee Lock + Tedee Bridge + Class 6 cylinder



Class 6 cylinder included

- ✓ Anti-theft lock cylinder. New design of the cylinder with protection against opening using the "bumping" method, an effective solution that protects against drilling.



Install the tedee lock

- ✓ Slide the lock over the GERDA cylinder, adjust the lock positions and fasten with one screw. It will not take more than 2 minutes. Check for loosened bolts after unscrewing the knob.



Install the application on your smartphone

- ✓ Download the tedee app from Apple Store or Google Play. Register and turn on Bluetooth, location service and internet access.



Connect bridge

- ✓ Find an available power outlet closest to the tedee lock and plug the bridge into it. This will allow you to fully control the lock via the Internet, no matter where you are.



Apartment and house entry doors

Our solutions for frames and door leaves are perfect for even the most demanding facilities. Our panel and metal doors can boast above-average robustness, functionality (e.g. the possibility of easy disassembly and replacement of the door panel) and freedom of arrangement.



Locks, cylinders and fittings

Safety first. High burglary resistance is achieved thanks to internal castings or heat-treated steel plates. The hardened cylinder cover protects against thrusting from hinges and prevents drilling through.

The general key system MASTER KEY is a solution dedicated to utility objects. Using one key you can open a specific number of locks. This makes communication inside the facility simple and fast, and managing access to zones and rooms is extremely comfortable.



Garage Doors

All garage doors available in our offer are in line with European standards. GERDA gates are equipped with a complete security system, without any additional charge.

Trend series gates are an economical, but robust and functional solution, perfect for development facilities.

Classic line doors guarantee exceptional thermal insulation, among others thanks to the use of insulated 45-mm thick panels. They will be perfect for buildings with high energy efficiency requirements.



Aluminum joinery

GERDA also deals with aluminum joinery. We provide partition walls, doors, windows, showcases and spatial internal and external installations, also in fire and smoke-proof versions and with increased burglary resistance.



Why choose GERDA Aluminum Doors?

GERDA ALTUS anti-burglary aluminum door has been designed to achieve the best possible thermal insulation parameters. Made of a three-chamber aluminum system with a thickness of almost 9 cm, they meet the strict requirements set for modern passive construction.

As standard, ALTUS doors are fit with a spacer made in the patented anti-bimetal technology, specially designed insulators significantly enhance the thermal insulation parameters and have a considerable impact on reducing energy consumption. Thermal compensation is the perfect solution to the deformation occurring in doors exposed to intense insolation. This technology is perfect for decorative fillings. In addition, the unique mounting of door hardware in the insulator ensures original design and unique aesthetic impressions. The structure of GERDA ALTUS aluminum doors allows for obtaining a uniform surface both from the inside and outside.

ALTUS doors are equipped with 5-point slat locks, guaranteeing sealing around the entire perimeter of the leaf, while ensuring safety of the household members. The stainless-steel face plate of the lock is what characterizes the premium product. For customers looking for an individual entrance, the offer of GERDA ALTUS doors has been enriched with the possibility of making a door leaf with a set of sidelights and upper skylight made of aluminum profiles ensuring excellent thermal insulation parameters.


ALTUS - provides exceptional thermal insulation, high stiffness, safety and comfort of use for years.



Thermal compensation


Types of door locks

The FUHR multipoint lock system with five locking points guarantees tightness around the entire perimeter of the leaf. A massive hook pin provides a top level of security and sash reinforcement. The lock is installed along the entire height of the door.



5-point hooked lock

FUHR automatic flat lock with three locking points ensures accurate closing. The robust mechanism guarantees over 200,000 cycles. Durable locking hooks and the main bolt ensure a top level of safety.



Automatic locking

Not available for RC3.

3-point automatic lock

As a standard.

Solid door

$U_D = 0.74 \text{ W/m}^2\text{K}$

Glazed door

$U_D = 0.81 \text{ W/m}^2\text{K}$


RC2 / RC3 CLASS

Class RC3 as an option



Overlay hinges

Overlay hinges in the color of the door leaf.



Roller hinges*

Roller hinges in the color of the door leaf.



Integrated hinges*



Door thickness




Door frame

Aluminum multi-chamber door frame with built-in compensators..



Pawl hitch

Adjustable pawl hitch.




Threshold

An insulated aluminum threshold with a thermal separator.



Frame thickness




Handrail*

Stainless-steel handrail mounted on the external side of the door.



Handle K1

Stainless steel handles with split escutcheon.



Fixed bolts

Fixed anti-prizing bolts.



Mortise lock

5 point hooked or 3 point automatic.



Ring escutcheon*

Ring escutcheon ensuring protection of the cylinders against forcing.



Handle K2*

Aluminum handles with long escutcheon.

* EXTRA CHARGE



ALTUS Door Collection



FLUSH DECOR

FE3

• RAL 1015

GLAZED FLUSH DECOR

GC3

• Anthracite, Dark Sapphire

FLAT

FA1

• RAL 7016



GLAZED FLUSH DECOR

GF2

• RAL 7021

MILLED WITH INSERT

FB4

• RAL 1015

MILLED WITH INSERT

FB5

• RAL 9016

Extra charges

tedee set

Class 6 cylinder

Handrail 1500 mm

Handrail 1500 mm with pushbutton

RC3 package

Roller hinges

Integrated hinges (only RC2)

K2 handle (RC2)

Integrated closer

Electric strike

Two-color doors

Double-sided design

Custom door size

+15% extra charge



FLAT

FA1



MILLED

FB1



MILLED

FB2






MILLED WITH INOX OR BLACK INSERT

FB4

FB4B



Colours






AVAILABLE
BLACK
ACCESSORIES

MILLED WITH INOX OR BLACK INSERT

FB5

FB5B



MILLED

FC1



MILLED

FD1



FLUSH DECOR

FE1

Extra charges

tedee set

Class 6 cylinder

Handrail 1500 mm

Handrail 1500 mm with pushbutton

RC3 package

Roller hinges

Integrated hinges (only RC2)

K2 handle (RC2)

Integrated closer

Electric strike

Two-color doors

Double-sided design

Custom door size

+15% extra charge

RAL 7016

RAL 9016

RAL 7021

RAL 1015

Anthracite
Light Sapphire

Anthracite
Dark Sapphire

Extra charges

tedee set

Class 6 cylinder

Handrail 1500 mm

Handrail 1500 mm with pushbutton

RC3 package

Roller hinges

Integrated hinges (only RC2)

K2 handle (RC2)

Integrated closer

Electric strike

Two-color doors

Double-sided design

Custom door size

+15% extra charge



FLUSH DECOR

FE2



FLUSH DECOR

FE3



GLAZED





GA1



GLAZED

GA2

Colours





GLAZED

GA 3



GLAZED WITH INOX OR BLACK APPLICATION

GB 1

GB 1B



GLAZED WITH INOX OR BLACK APPLICATION

GB 2

GB 2B



GLAZED WITH INOX OR BLACK APPLICATION

GB 3

GB 3B

Extra charges

tedee set

Class 6 cylinder

Handrail 1500 mm

Handrail 1500 mm with pushbutton

RC3 package

Roller hinges

Integrated hinges (only RC2)

K2 handle (RC2)

Integrated closer

Electric strike

Two-color doors

Double-sided design

Custom door size

+15% extra charge

RAL 7016

RAL 9016

RAL 7021

RAL 1015

Anthracite Light Sapphire

Anthracite Dark Sapphire

Extra charges

tedee set

Class 6 cylinder

Handrail 1500 mm

Handrail 1500 mm with pushbutton

RC3 package

Roller hinges

Integrated hinges (only RC2)

K2 handle (RC2)

Integrated closer

Electric strike

Two-color doors

Double-sided design

Custom door size

+15% extra charge



GLAZED FLUSH INOX OR BLACK DECOR

GC1



GLAZED FLUSH INOX OR BLACK DECOR

GC2



GLAZED FLUSH INOX OR BLACK DECOR





GC3



GLAZED MILLED

GD1

Colours





GLAZED MILLED

GD 2



GLAZED MILLED

GD 3



GLAZED MILLED WITH INOX OR BLACK INSERT

GD 4

GD 4 B



GLAZED MILLED WITH INOX OR BLACK INSERT

GD 5

GD 5 B

Extra charges

tedee set

Class 6 cylinder

Handrail 1500 mm

Handrail 1500 mm with pushbutton

RC3 package

Roller hinges

Integrated hinges (only RC2)

K2 handle (RC2)

Integrated closer

Electric strike

Two-color doors

Double-sided design

Custom door size

+15% extra charge

RAL 7016

RAL 9016

RAL 7021

RAL 1015

Anthracite Light Sapphire

Anthracite Dark Sapphire

Extra charges

tedee set

Class 6 cylinder

Handrail 1500 mm

Handrail 1500 mm with pushbutton

RC3 package

Roller hinges

Integrated hinges (only RC2)

K2 handle (RC2)

Integrated closer

Electric strike

Two-color doors

Double-sided design

Custom door size

+15% extra charge



GLAZED MILLED WITH INOX OR BLACK INSERT

GD 6 GD 6 B



GLAZED MILLED

GE 1



GLAZED MILLED





GE 2




GLAZED MILLED

GE 3

Colours





AVAILABLE
BLACK
ACCESSORIES

GLAZED MILLED WITH INOX OR BLACK INSERT

GE4

GE4B



AVAILABLE
BLACK
ACCESSORIES

GLAZED MILLED WITH INOX OR BLACK INSERT

GE5

GE5B



AVAILABLE
BLACK
ACCESSORIES

GLAZED MILLED WITH INOX OR BLACK INSERT

GE6

GE6B



GLAZED FLUSH DECOR

GF1

Extra charges

tedee set

Class 6 cylinder

Handrail 1500 mm

Handrail 1500 mm
with pushbutton

RC3 package

Roller hinges

Integrated hinges
(only RC2)

K2 handle (RC2)

Integrated closer

Electric strike

Two-color doors

Double-sided design

Custom door size

+15% extra charge

RAL 7016

RAL 9016

RAL 7021

RAL 1015

Anthracite
Light Sapphire

Anthracite
Dark Sapphire

Extra charges

tedee set

Class 6 cylinder

Handrail 1500 mm

Handrail 1500 mm with pushbutton

RC3 package

Roller hinges

Integrated hinges (only RC2)

K2 handle (RC2)

Integrated closer

Electric strike

Two-color doors

Double-sided design

Custom door size

+15% extra charge



GLAZED FLUSH DECOR

GF 2



GLAZED FLUSH DECOR




GF 3



GLAZED MILLED

GH 1


Colours






Dimensions of door frames

Horizontal cross-section



Vertical cross-section



Legenda:

- Hp – height of passage
- Sp – width of passage with door opened 90°
- Hc – total height of door frame
- Sc – total width of door frame
- Hm – recommended height of mounting hole from the "0" level
- Sm – recommended width of mounting hole
- So – width of passage of the door frame

Doors with overlay hinges

Size	Hp	Sp	So	Hc	Sc	Hm*	Sm**
90N	2004 mm	726 mm	818 mm	2100 mm	970 mm	2110 mm	990 mm
90E	2004 mm	906 mm	998 mm	2100 mm	1150 mm	2110 mm	1170 mm

Doors with roller hinges

Size	Hp	Sp	So	Hc	Sc	Hm*	Sm**
90N	2004 mm	738 mm	818 mm	2100 mm	970 mm	2110 mm	990 mm
90E	2004 mm	918 mm	998 mm	2100 mm	1150 mm	2110 mm	1170 mm

Doors with integrated hinges

Size	Hp	Sp	So	Hc	Sc	Hm*	Sm**
90N	2004 mm	784 mm	818 mm	2100 mm	970 mm	2110 mm	990 mm
90E	2004 mm	964 mm	998 mm	2100 mm	1150 mm	2110 mm	1170 mm

Non-standard door size – pitch of 5 mm (with overlay hinges)

Size	Hp	Sp	So	Hc	Sc	Hm*	Sm**
min.	1904 mm	726 mm	818 mm	2000 mm	970 mm	2010 mm	990 mm
maks.	2304 mm	1006 mm	1098 mm	2400 mm	1250 mm	2410 mm	1270 mm

* includes a clearance of 10 mm in height
 ** zawiera luz montażowy 10 mm on sides

In order to calculate the dimensions of the mounting hole for a set of doors fit with a side light, the external dimension of the selected side light must be added to the external dimensions of the door and clearance must be kept.



GL set



G set



GP set



LGP set



L set



LP set



P set

Side light*

Door height	Type of glass	Width	
		300-500 mm	550-700 mm
up to 2100 mm	Safe	✓	✓
	P4	✓	✓
	P5	✓	✓
up to 2400 mm	Safe	✓	✓
	P4	✓	✓
	P5	✓	✓

* Side lights, standard width in a 50 mm pitch. An additional cost of 25% in a pitch of 10 mm.

* Side lights, standard height in a pitch of 5 mm.

* Glazing, matte.

Top light*

Height of illumination	Type of glass	Width		
		up to 1250 mm	up to 1950 mm	up to 2650 mm
300-500 mm	Safe	✓	✓	✓
	P2	✓	✓	✓
	P4	✓	✓	✓

* Top lights standard height in a pitch of 50 mm. An additional cost of 25% in a pitch of 10 mm.


* Top lights, standard width in a pitch of 5 mm.

* Glazing, matte.

Basic colours




RAL 7016



RAL 9016



RAL 1015



Anthracite light sapphire



RAL 7021




Anthracite dark sapphire


Flushed wood-like decor




Golden oak FDE




Winchester FDW



Turner oak FDT



Light wenge FEJ



Alpine walnut FRR

Flushed INOX decor



Brushed INOX




Black RAL 9005


Glazing*



Clear glass



Matte glass



Matte glass & see-through stripes




Reflex Brown glass



Reflex Graphite glass

























Reflex Black glass



Mira Star Mirror

* Glazing in the Altus offer in the standard version is built on two-chamber packages with P4 panes with the so-called warm inter-pane frames guaranteeing a minimum heat transfer coefficient $U_d = 0,5$ W/m²K.

	Class 5 cylinder Class 6 cylinder		Electronic viewer 2,4"
	Class 5 cylinder with knob Class 6 cylinder with knob		Electronic viewer 4,3"
	K1 double-sided handle with split escutcheon		Access control numeric key pad
	K1 single-sided handle with split escutcheon		Buffer power supply unit
	K1 handle-knob with split escutcheon		Switching power supply unit
	K1 split escutcheon with lock cylinder protection		Side extension 20 mm
	K2 double-sided handle with long escutcheon		Side extension 34 mm
	K2 single-sided handle with long escutcheon		Side extension 48 mm
	Handrail 1500 mm Handrail 1700 mm Handrail 1800 mm		Side extension 100 mm
	Handrail with push button 1500 mm Handrail with push button 1700 mm Handrail with push button 1800 mm		Corner 90°
	Integrated hinges		Under threshold extension 30 mm Under threshold extension 50 mm Under threshold extension 70 mm Under threshold extension 100 mm
	Roll hinges		Lock and cylinder maintenance agent 25 ml Lock and cylinder maintenance agent 100 ml Lock and cylinder maintenance agent 400 ml
	Integrated door closer		Gerda Resist ultra insulation duo tapes
	INOX maintenance agent		Adjustment for handrail with pushbutton



Inspirations

ALUMINUM DOORS







Inspirations

ALUMINUM DOORS



ALUMINUM DOORS

Inspirations





Gerda Sp. z o.o.

Sokołów, ul. Sokołowska 49

05-806 Komorów

Poland

Phone: (+48) 22 329 10 30

e-mail: export@gerda.pl

www.gerda.pl

This catalogue does not constitute an offer under the provisions of law and is merely informational.

Gerda Sp. z o.o., committed to continuously improving its products and services, reserves the right (without prior notice) to introduce changes to products that, due to the printing material preparation process, may not be included in this material.

Despite all the effort and care in controlling the presented content, substantial or printing errors may occur.

Colours presented herein may differ from the original due to different colour reproduction technique in the printing process. The owner of the copyright for this catalogue, as well as Gerda Sp. z o.o. logotypes and graphics, is Gerda Sp. z o.o.

It is prohibited to copy or distribute any content and material without the prior consent of Gerda Sp. z o.o.